



Compact, professional MPEG player for MPEG-2 and MPEG-1 video clips, JPEG pictures and MP3 audio files.

Applications:

Point of Information / Point of Sale (e.g. in museums, retail shops, public service offices, etc.), presentations in museums, theme parks, advertising.

The ProPLAY is a cost-effective, professional solution for applications where budgetary considerations are important. Any application in which video, audio and pictures on-demand are needed is an application for the ProPLAY.

Clips are stored on the compact flash card, so playback is virtually instantaneous. Clips may be triggered using external contacts, serial RS-232 commands, or by programming a playlist with the user-friendly windows software. The ProPLAY can also simply loop continuously.

The windows setup software is versatile and rich in features, making it possible for you to program the ProPLAY to run even complex and demanding shows and events.

Features:

- Storage and playback of MPEG-2 or MPEG-1 encoded clips
- Storage and playback of single MPEG frames; JPEG pictures and MP3 audio files
- Control per playlist, RS-232 and contact closure (max. 8 contacts)
- Files are stored on compact flash cards up to 4 GB (not included)
- Outputs PAL / NTSC video signal through the S-Video, Composite and VGA outputs
- Stereo audio RCA output
- Loudspeaker output (1 W/8 Ω; 2 W/4 Ω)
- Lockable CF-Card Slot
- USB Port

Model: ProPLAY

Manufacturer: COMM-TEC



Technical Details

Type:	Video Player
Model:	ProPLAY
Cat. No.	711023
Front	
Video outputs	VGA (15-pin sub-D) S-Video (Mini DIN) Composite video (RCA)
Audio outputs	Analog stereo, (RCA) Loudspeaker output, 15-pin sub-D
Control	RS-232 port, 15-pin sub-D Contact closure, 15-pin sub-D
Other	power input, 2,5 mm mini connector PAL / NTSC selector switch Video/VGA selector switch
Rear	
Storage	Compact-flash socket, accepts Type I or Type II; max. 4 GB CF-Card Mini USB Port (2.0)
Video	MPEG-2 clips, maximum bit rate 8 Mbit/s MPEG-1 clips, maximum bit rate 1,5 Mbit/s JPEG, maximum resolution 800 x 600
Audio	MP3, encoded at a data rate of between 16 – 256 kBit/s
Audio specifications	Analog Stereo Output of 1W / 8 Ω, (2W / 4 Ω) 96 dB signal/noise ratio
Dimensions	187 x 26 x 108 mm (W x H x D)
Weight	approximately 400 grams
Power	External power supply, 230 V / 12 V DC
Power consumption	maximum 6 W
Environmental Operating Conditions	0° – 50° Celsius (with proper air circulation) 5% – 95% relative humidity
Included in delivery	Operation Manual, power supply and cord, 15-pin sub-D Connector
Required accessories (not included in delivery)	Compact Flash card, ProPLAY Studio software to produce material and for show-control programming (software required only 1 x per customer/per project) Cat. No. 711025
Optional accessories	Mounting board for mounting to standard VESA displays Cat. No. 711029 or Upside-down Cat. No. 711028

Specifications are subject to change without notice. Mechanical dimensions may vary.